



# LEED Specification Sheet DURAPRO AW3466

October 2021

To Whom It May Concern:

The use of DURAPRO AW3466 PVA TYPE 2 Wood Glue could be contributing LEED credits from the Canadian Green Building Council Rating System for New Construction & Major Renovations as follow:

## IEQc3.2: Construction IAQ management plan – Testing before occupancy

Low VOC content of DURAPRO AW3466 can contribute to air quality test.

### IEQc4.1: Low-emitting materials – adhesives & sealants

DURAPRO AW3466 content of VOC is more than 30 g/L less water, therefore not meeting the requirement of South Coast Air Quality Management District (SCAQMD) Rule No.1168. DURAPRO AW3466 do not contain VOC in excess of 5% by weight.

# IEQc4.4: Low-emitting materials - composite wood and laminate adhesives

DURAPRO AW3466 contains no urea-formaldehyde resin added and can be used in the composition of assemblies produced on site and in the workshop.

## IEQc4.5: Low-emitting materials - furniture and furnishings

DURAPRO AW3466 contains no urea-formaldehyde resin added and can be used in the composition of assemblies produced on site and in the workshop.

#### MRc2: Construction waste management

Packaging of DURAPRO AW3466 is made of recoverable and recyclable materials and can be collected for treatment where facilities exist.

#### MRc5.1 and 5.2: Material and Resource - Regional materials

When used in a project site within 800 kilometers (or 2400 kilometers if shipped by rail or water) from the manufacturing plant located at Dorval, Quebec.

# MRc6: Rapidly renewable materials

DURAPRO AW3466 includes rapidly renewable materials.

This statement is based on the product referenced above and the formulation of the product and the regulations in place according to the date of this letter.

Please use this letter for specification purposes. For a copy of the SDS or TDS, contact your Dural sales representative, email at <a href="mailto:durapro@dural.ca">durapro@dural.ca</a> or call 1-800-361-2340.