

AF0036

SOFT FLOOR COVERING ADHESIVE

PRODUCT DESCRIPTION

DURAPRO AF0036 is a non-flammable interior flooring adhesive for bonding carpet and sheet covering over plywood underlayment or well cured concrete.

PRODUCT FEATURES

- Easy to spread
- High tack
- Non-flammable

PREPARATION

Surface must be structurally sound, linear, clean, dry and free of contaminants. Substrate, floor material (unwrapped and flattened) and adhesive must be acclimated at the same temperature and humidity level expected during normal use (between 15°C and 25°C, RH not exceeding 65%). Concrete floors must be fully cured and free from moisture and hydrostatic pressure.

APPLICATION

Stir before using. Spread adhesive with a 1.5 mm (1/16") V notch trowel held at 45° angle for smooth backing. For floor covering with rough backing use a 4.5 mm (3/16") V notch trowel. Spread the adhesive and put the floor covering in place within 30 minutes. Lay the flooring material as per manufacturer's instructions. Use a 45 kg (100 lbs) roller in several directions to eliminate trowel marks and air entrapment, and to ensure optimal transfer of the adhesive. Let dry 24 hours before allowing heavy foot traffic or moving furniture.

COVERAGE

1 Liter covers approximately 2-4 m² (80-160 sq.ft./gallon) in surface area.

ATTENTION

Consult industry standards. Follow all appropriate building code requirements. Refer to flooring manufacturer's recommendation for layout, expansion space requirements, and detailed installation instructions. For indoor use only. Not to be used on particleboard.

PHYSICAL PROPERTIES

Viscosity	60,000 – 70,000 cps (RVT, #7/20 rpm/25°C)
Solids	54 – 56 %
Colour	Light tan
Odour	Hydrocarbon
Specific Gravity	1.25
pH	6.5 – 7.5
Open time (low temperature and high humidity increases drying time)	30- 40 minutes
VOC calculated (SCAQMDR 1168) (Ecologo UL2762)	< 50 g/L less water < 5 % per weight
Water-resistance	Excellent (when dried)

CLEAN-UP

Clean hands and tools immediately after use with warm water. If adhesive has dried, use an adhesive cleaner or mineral spirits with caution, taking care not to affect the surface finish.

STORAGE

Store indoor in a cool, dry location between 10°C and 35°C. Keep container closed when not in use. Protect from freezing. Product is freeze-thaw stable if frozen not lower than -10°C in transit.

SHELF LIFE

Shelf life is 18 months at room temperature in original unopened container.

DISPOSAL

Consult your municipality to dispose container and left-over in accordance with environmental regulations.

PACKAGING

Item code	Size	Units per case	Units per row	Units per pallet
AF0036-950	950 ml	6	72	432
AF0036-378	3.78 L	2	20	100
AF0036-015	15 L	1	16	48

ENVIRONMENT

This product contains no added urea-formaldehyde. The use of this product may contribute in obtaining LEED credits. Product certified for reduced environmental impact (ECOLOGO UL2762).

PRECAUTIONS

Keep out of reach of children. May cause slight eye and skin irritations. Avoid contact with eyes and skin. **FIRST AID TREATMENT:** If in eyes or on skin, rinse the affected areas with water. If swallowed, drink water and call a doctor. **For industrial user – Refer to Safety Data Sheet (SDS) for further information.**

LOT CODE

Lot code (batch number) is stamped on the lid or on the side panel of the container. Code consists of 6 digits: 2 letters and 4 numbers

1st letter = last number of the year of production corresponding to the sequential alphabetical order (excluding I and J) (starts over at A every decade) ;

2nd letter = indicates the month of production corresponding to the sequential alphanumeric order (excluding I and J) ;

4 numbers = sequential batch number starting by 0001 on the 1st day of production in the annual calendar year.

Example: KA0123

1st letter: K = 2019

2nd letter: A = January

4 digits = 0123 = 123th batch produce since January 1, 2019

WARRANTY

Surface conditions, product application, storage and transport are beyond the manufacturer's control; liability, if any, is limited to the replacement of product ONLY. Product made and labeled for sale and use in CANADA only.

DISCLAIMER

Our personal is available to help purchasers obtain best results from our products, and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on conditions that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision.

TECHNICAL SERVICES

Technical assistance is available by phone at 800-361-2340 or email at durapro@dural.ca

To acquire technical and safety literature, please visit our website at www.duraproadhesives.com .

REVISION DATE

February 2020

MANUFACTURED BY

Dural, division of MULTIBOND Inc.

550 Marshall avenue,

Dorval, Qc CANADA H9P 1C9

