

AC1844

PREMIUM CONTACT CEMENT

PRODUCT DESCRIPTION

DURAPRO AC1844 is a neoprene rubber adhesive used for bonding decorative laminates (Arborite, Formica), wood and plastic veneers, paneling, cork, carpet, fabrics, sheet metal and other combinations of these to wood, plywood, particle board or metal. Forms a durable permanent bond when parts are assembled and momentary pressure is applied.

PRODUCT FEATURES

- Superior strength
- Non drip
- Heat resistant

PREPARATION

Stir well until uniform consistency. Adhesive and materials (unwrapped) must be at room temperature (20°C) 24 hours before, during and after installation. All surfaces to be glued must be clean, dry and free of irregularities. Remove all paint, varnish, grease, oil, dust, sawdust and other foreign materials. Pre-fit parts before applying adhesives.

APPLICATION

Apply a uniform coat of adhesive to both surfaces using a solvent resistant soft brush or short nap roller. Porous surfaces such as trim strips may require two coats. Allow to dry until 5 to 20 minutes until the film is glossy and tacky, without adhesive transferring to the finger when touched. Within the next 30 minutes, place both surfaces in exact position and join them carefully. The bond is instant on contact and surfaces cannot be repositioned. Using a metal roller or rubber mallet, apply firm pressure over entire surface, working from center toward the edges to eliminate any air pockets. Roll in two directions at 90° angles to each other. Adhesion strength will increase with aging, but edges can be cut for finishing immediately. Let cure at least 3 days before exposure to direct sunlight or high temperatures.

COVERAGE

1 Liter covers approximately 3 m² (120 sq.ft./gallon in surface area or 60 sq.ft./gallon of bonded surface).

Note: Yields shown are based on theoretical calculations for comparison purposes and may vary depending on particular conditions on the jobsite. Porous surfaces and substrates may require more adhesive than the typical coverage rate.

PHYSICAL PROPERTIES

Viscosity	1,600 - 1,700 cps (4/20 rpm/25°C)
Solids	21.5 – 22.5 %
Colour	Amber
Odour	Ketone when wet No odor when dry
Specific Gravity	0.83
Drying time (low temperature and high humidity increases drying time)	Work time: 5 - 20 minutes Cure time: 7 days
Flash Point	-18°C

CLEAN-UP

Clean hands and tools immediately after use with toluene.

STORAGE

Store indoor in a cool, dry location between 10°C and 35°C. Keep container closed when not in use. Store off the floor. Protect from freezing. Product is freeze-thaw stable to -10°C. Avoid prolonged or repeated freeze thaw cycles. Should product freeze, do not open the container, allow to thaw at room temperature and stir well before using.

For more details, refer to Safety Data Sheet (SDS).

SHELF LIFE

Shelf life is 18 months at room temperature in original unopened container.

DISPOSAL

Consult your municipality to dispose container and left-over in accordance with environmental regulations.

ENVIRONMENT

This product contains no added urea-formaldehyde resin. The use of this product may contribute in obtaining LEED credits.

PACKAGING

Item code	Size	Units per Case	Units per Row	Units per Pallet
AC1844-378	3.78 L	2	36	180
AC1844-189M	18.9 L	1	16	48
AC1844-MD	205 L	1	4	4

PRECAUTIONS

CONTENTS HARMFUL. CONTENT MAY CATCH FIRE. MAY IRRITATE EYES. MAY IRRITATE SKIN. Do not mix with other household chemicals. Do not swallow. Wear a mask. Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children. Do not smoke. Keep away from flames, such as pilot light and any objects that spark, such as an electric motor. Use only in a well-ventilated area. Use a tool such as a screwdriver to open the container. Close container after each use. **First Aid Treatment:** Contains Acetone, Hexane, Toluene, 3-Methylpentane, 2-Methylpentane. If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for at least 15 minutes. If on skin, rinse well with water. If breathed in, move person to fresh air. REFER TO SAFETY DATA SHEET (SDS) FOR MORE INFORMATION.

LOT CODE

Lot code (batch number) is stamped on the lid or side panel of the container. Code consists on 6 digits.

1st and 2nd digits = last 2 numbers of the year of production.

3rd and 4th digits = correspond to the month of production.

5th and 6th digits = sequential batch number starting by 01 on the 1st day of production in the monthly calendar.

Example: 191215

1st and 2nd digits = 19 = 2019

3rd and 4th digits = 12 = December

5th and 6th digits = 15 = 15th batch produce since December 1

WARRANTY

Surface conditions, product application, storage and transport are beyond the manufacturer's control; liability, if any, is limited to the replacement of product ONLY. Product made for sale and use in Canada.

DISCLAIMER

Our personal is available to help purchasers obtain best results from our products, and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on conditions that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision.

TECHNICAL SERVICES

Technical assistance is available by phone at 800-361-2340 or email at durapro@dural.ca

To acquire technical and safety literature, please visit our website at www.dural.ca

REVISION DATE

January 2020

MANUFACTURED BY

Dural, division of MULTIBOND Inc.

550 Marshall avenue, Dorval, Quebec, CANADA H9P 1C9