

AF2607

FLOATING FLOOR ADHESIVE

PRODUCT DESCRIPTION

DURAPRO AF 2607 is an adhesive specially designed for the floating installation of engineered wood or laminated floors over cured concrete, T&G floor grade plywood, particle board, acoustic membranes or radiant heat systems either, on above, or below grade.

PRODUCT FEATURES

- Water-resistance PVA Type II
- Siliconized glue
- Easy clean up

PREPARATION

Mix well before using. Adhesive, material and room temperature should be between 15°C and 25°C. All surfaces to be glued must be clean and dry. Make sure the groove of the plank is free of dust and debris. Best bonds are obtained when moisture content of wood ranges between 8% and 12%.

APPLICATION

Apply directly from the plastic bottle. Apply adhesive generously along the entire length of the groove. Spread glue to result in squeeze out when parts are assembled. Joints must be tight fitting. Fit the planks tightly using a rubber mallet and by following the laying instructions from the flooring manufacturer. When glue becomes colorless, remove the excess by lifting the dry film slowly. Let dry 24 hours before allowing heavy foot traffic or moving furniture.

COVERAGE

1 bottle (518ml) covers approximately 121 linear metres (400 linear feet) equivalent to 14 m² (150 sq.ft.) in surface area with planks of 9 cm (3 ½") width.

PHYSICAL PROPERTIES

Viscosity	4,000 – 5,000 cps (5/20 rpm/25°C)
Solids	48 – 50 %
Colour	White when wet Transparent when dry
Odour	Mild when wet No odour when dry
Specific Gravity	1.06
Assembly time	5 minutes
VOC calculated (SCAQMDR 1168) (Ecologo UL2762)	< 100 g/L less water < 5 % per weight

ATTENTION

Consult industry standards. Follow all appropriate building code requirements. Refer to wood flooring manufacturer's recommendation for layout, expansion space requirements, and detailed installation instructions. Must dry 5 hours before exposing to water or humidity.

CLEAN-UP

Clean hands and tools immediately after use with warm water. If adhesive has hardened, remove by lifting the dry film.

STORAGE

Store indoor in a cool, dry location between 10°C and 35°C. The stability of AF2607 is optimum when stored between 5°C and 15°C. Keep container closed when not in use. Protect from freezing. Product is freeze-thaw stable if frozen not lower than -10°C in transit.

SHELF LIFE

Shelf life is 18 months at room temperature in original unopened container. Viscosity of AF2607 will increase with time, but as long as the material can be stirred to a smooth consistency it is satisfactory to use.

PACKAGING

Item code	Size	Units per case	Units per row	Units per pallet
AF2607-518	518 ml	8	160	800

AF2607

FLOATING FLOOR ADHESIVE

DISPOSAL

Consult your municipality to dispose container and left-over in accordance with environmental regulations.

ENVIRONMENT

This product contains no added urea-formaldehyde resin. The use of this product may contribute in obtaining LEED credits. Product certified for reduced environmental impact (ECOLOGO UL2762).

PRECAUTIONS

Keep out of reach of children. May cause slight eye and skin irritations. Avoid contact with eyes and skin. **FIRST AID TREATMENT:** If in eyes or on skin, rinse the affected areas with water. If swallowed, drink water and call a doctor. **For industrial user – Refer to Safety Data Sheet (SDS) for further information.**

LOT CODE

Lot code (batch number) is stamped on the lid or on the side panel of the container. Code consists of 6 digits: 2 letters and 4 numbers

1st letter = last number of the year of production corresponding to the sequential alphabetical order (excluding I and J) (starts over at A every decade) ;

2nd letter = indicates the month of production corresponding to the sequential alphanumeric order (excluding I and J) ;

4 numbers = sequential batch number starting by 0001 on the 1st day of production in the annual calendar year.

Example: LA0123

1st letter: K = 2020

2nd letter: A = January

4 digits = 0123 = 123th batch produce since January 1, 2020

WARRANTY

Surface conditions, product application, storage and transport are beyond the manufacturer's control; liability, if any, is limited to the replacement of product ONLY. Product made for sale and use in Canada only.

DISCLAIMER

Our personal is available to help purchasers obtain best results from our products, and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on conditions that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision.

TECHNICAL SERVICES

Technical assistance is available by phone at 800-361-2340 or email at durapro@dural.ca

To acquire technical and safety literature, please visit our website at www.dural.ca and www.duraproadhesives.com .

REVISION DATE

January 2021

MANUFACTURED BY

Dural, division of MULTIBOND Inc.

550 Marshall avenue,

Dorval, Qc CANADA H9P 1C9

