

DURA PRO[®]

a Dural brand



Glues & Adhesives For Building Materials



PRODUCT CERTIFIED FOR
REDUCED ENVIRONMENTAL
IMPACT. VIEW SPECIFIC
ATTRIBUTES EVALUATED.
UL.COM/EL
UL 2762



www.duraproadhesives.com

DURAPRO[®]

a Dural brand

*Since
1952*

Dural has been manufacturing adhesives and polymers for over 65 years. It is through this experience and the fact that we manufacture and control many of our own base polymers, that we are able to offer our clientele trouble-free adhesives of the highest possible quality at reasonable prices.

Each container of DURAPRO's adhesive is the result of years of formulating, producing and marketing by a team of highly qualified and experienced technical people. Our close liaison with customers, customer needs, and changing market conditions have added to the growth of DURAPRO a Dural brand.

It is this total commitment to service that has placed the name Dural high on the list of preferred suppliers for major industrial companies and retailers across Canada. We are ISO certified; we offer the most complete line of adhesives certified **ECOLOGO by UL Environment**; and, today, we are pleased to be a participant to "WELL MADE HERE" - a program to encourage the purchase of quality building materials and other items manufactured in Canada and intended for the residential market. The essentials for a PRO job.

Since 1952, Dural has evolved from a local adhesive manufacturer to a global vertically integrated manufacturer of adhesives and polymers as part of the CFS Group Inc., with 15 plants and warehouses around the world.











Dural, a division of MULTIBOND Inc., is a privately owned and operated Canadian company. The corporate Head Office is located in Dorval Quebec.



THE ESSENTIALS FOR A PRO JOB

AC SERIES










Construction & Panel Adhesives

AC 1920		<p>Contact cement (solvent)</p> <ul style="list-style-type: none"> • For HPL, veneers, corner beads and rubber stair treads • No clamp • Instant bond • Brush grade 	<p>Available sizes</p> <p>205 L 18.9 L 3,78 L 950 ml 236 ml</p>
AC 1875		<p>Contact cement (solvent)</p> <ul style="list-style-type: none"> • For HPL, veneers • Spray grade • Instant bond • No clamp • Tinted red (AC1875) • Clear (AC2095) 	<p>Available sizes</p> <p>205 L 18.9 L</p>
AC 2095			
AC 1844		<p>Premium Contact cement</p> <ul style="list-style-type: none"> • For HPL, veneers, corner beads and rubber stair treads • No clamp • Instant bond • Brush grade • Superior strength • Non-drip • Heat-resistant 	<p>Available sizes</p> <p>205 L 18.9 L 3,78 L 950 ml</p>
AC 2389		<p>Contact cement (latex)</p> <ul style="list-style-type: none"> • For HPL, cork, veneers, stair treads, vinyl, rubber • Water base adhesive • Low odor • High coverage • Non flammable • ECOLOGO UL2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>205 L 18.9 L 3,78 L 950 ml</p>
AC 3471		<p>Latex Contact Cement</p> <ul style="list-style-type: none"> • For HPL and veneers • Brush, roller and spray application • Solvent free • Low odor • Heat resistant 	<p>Available sizes</p> <p>15 L 3,78 L 950 ml</p>
AC 0055		<p>Construction & Panel Adhesive</p> <ul style="list-style-type: none"> • For bonding drywall, decorative panels, FRP and NRP panels • Fast tack • Latex base adhesive • Non flammable • Strong bond • CAN/CGSB 71.25-M88, 71.26-M88, 71-GP-24M • ECOLOGO UL2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>15 L 3,78 L 950 ml</p>
AC 0054		<p>Foamboard adhesive</p> <ul style="list-style-type: none"> • For bonding insulation boards • High grab • Gap filling • Does not damage polystyrene • CAN/CGSB 71-GP-24M • ECOLOGO UL2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>15 L 3,78 L 950 ml</p>
AC 0616		<p>Concrete weld</p> <ul style="list-style-type: none"> • Indoor/outdoor • Water-resistant • Improves adhesion • Reduces cracking • ECOLOGO UL2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>205 L 18.9 L 4 L 1 L</p>
AC 3491		<p>Noiseproofing Compound</p> <ul style="list-style-type: none"> • Reduces sound transmission • Permanently flexible • Viscoelastic • Used in drywall, plywood and OSB assemblies • Passed ASTM E492 test 	<p>Available sizes</p> <p>15 L 3,78 L 950 ml</p>

THE ESSENTIALS FOR A PRO JOB

AF SERIES

Flooring Adhesives

AF 2607		<p>Floating floor adhesive</p> <ul style="list-style-type: none"> • For tongue & groove application • ANSI Type II water-resistance • Siliconized PVA • Easy Clean-up • ECOLOGO UL-2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>205 L 518 ml</p>
AF 0032		<p>Natural wood parquet adhesive</p> <ul style="list-style-type: none"> • For unfinished mosaic parquetry • For bonding plywood to plywood • Excellent adhesion • Non-flammable • ECOLOGO UL-2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>15 L 3,78 L</p>
AF 0034		<p>Prefinished parquet adhesive</p> <ul style="list-style-type: none"> • Rapid set • High solids • Excellent adhesion • Non-flammable • ECOLOGO UL-2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>15 L 3,78 L 950 ml</p>
AF 8839		<p>Engineered wood flooring adhesive</p> <ul style="list-style-type: none"> • For 3 and 5 ply engineered floors and exotic wood parquet • For acoustical membranes • Viscoelastic properties • High tack • Solvant free • ECOLOGO UL-2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>15 L 3,78 L 950 ml</p>
AF 0031		<p>Vinyl tiles & planks adhesive</p> <ul style="list-style-type: none"> • For direct and double glue-down installation • Wet lay and pressure sensitive characteristics • For acoustical membranes • Viscoelastic properties • For permanent or temporary installation 	<p>Available sizes</p> <p>15 L 3,78 L 950 ml</p>
AF 0036		<p>Soft floor covering adhesive</p> <ul style="list-style-type: none"> • For cushionfloor, carpet, cork • Easy to spread • High tack • Non-flammable • ECOLOGO UL-2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>15 L 3,78 L 950 ml</p>
AF 0044		<p>Ceramic tile adhesive</p> <ul style="list-style-type: none"> • ANSI A136.1 , CGSB 71-GP-22M, ISO 13007 D1TE • For tiles up to 8" x 8" and mesh-mounted mosaic • Easy to spread • For walls, floors, backsplashes and countertops • Type 1 water-resistance • Non-flammable • ECOLOGO UL-2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>15 L 3,78 L 950 ml</p>
AF 0038		<p>Outdoor carpet adhesive</p> <ul style="list-style-type: none"> • For outdoor carpet, synthetic turf • High tack • Solvent free • Weather-resistant 	<p>Available sizes</p> <p>15 L 3,78 L 950 ml</p>
AF 3490		<p>Pressure sensitive adhesive</p> <ul style="list-style-type: none"> • Permanent or releasable bond • High shear strength • Plasticizer migration resistant • Suitable for double glue-down installation with acoustical membrane 	<p>Available sizes</p> <p>15 L 3,78 L 950 ml</p>

THE ESSENTIALS FOR A PRO JOB

AM SERIES





Membrane Adhesives

AM 0220		Vinyl decking membrane adhesive <ul style="list-style-type: none">• To bond fleece and fabrics decking membrane• High tack• Brush or roller applied• Weather-resistant	Available sizes <ul style="list-style-type: none">18.9 L3.78 L950 ml
AM 0240		Premium Vinyl Decking Adhesive <ul style="list-style-type: none">• To bond fleece and fabrics decking membrane• Aggressive Grab Tack• Brush or roller applied• Weather-resistant	Available sizes <ul style="list-style-type: none">18.9 L3.78 L
AM 0295		Vinyl decking membrane adhesive <ul style="list-style-type: none">• To bond fleece and fabrics decking membrane• Fast dry• Brush or roller applied• Weather-resistant	Available sizes <ul style="list-style-type: none">18.9 L3.78 L950 ml
AM 3274		Overlap cement <ul style="list-style-type: none">• To seal joints and overlapped membranes, fabrics and some plastics• Fast dry• Non-yellowing	Available sizes <ul style="list-style-type: none">236 ml
AM 3275		Vinyl decking membrane adhesive <ul style="list-style-type: none">• To bond fleece and smooth back PVC membranes• Water-based• Single sided, wet-lay application• High-strength bond	Available sizes <ul style="list-style-type: none">18.9 L3.78 L
AM 3452		Waterproofing liquid membrane <ul style="list-style-type: none">• Ready-to-use, liquid• Brush, roller or trowel applied• No reinforcement fabrics required• Vapor barrier waterproofing• Provides crack isolation• Can be applied on OSB, MGO, cement board	Available sizes <ul style="list-style-type: none">18.9 L3.78 L
AM 3529		PVC membrane adhesive <ul style="list-style-type: none">• For smooth back PVC membranes• Contact type adhesive• Plasticizer resistant• Weather-resistant	Available sizes <ul style="list-style-type: none">18.9 L3.78 L
AM 3542		PVC membrane adhesive <ul style="list-style-type: none">• Single-side & double-sided application• For horizontal applications• High-strength bond• Excellent weather-resistance	Available sizes <ul style="list-style-type: none">18.9 L3.78 L
AM 6230		Multiple membrane adhesive <ul style="list-style-type: none">• High performance solvent free adhesive• For bonding many acoustical membranes, uncoupling membranes, fleeced or smooth back membranes, cork or felt underlayment• Trowel or roller application• High coverage	Available sizes <ul style="list-style-type: none">15 L3.78 L

THE ESSENTIALS FOR A PRO JOB

AW SERIES

Woodworking Glues

AW 4400		<p>Multipurpose White Glue</p> <ul style="list-style-type: none"> • Dries clear • Strength 3,000 Lbs • Assembly time: 5-10 minutes • High solids • Clamp time: 20-30 minutes • Non-staining • ECOLOGO UL-2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>205 L 18.9 L 4 L 1 L 518 ml 135 ml</p>
AW 2300		<p>Woodworker's glue (yellow)</p> <ul style="list-style-type: none"> • High initial tack • Excellent sandability • Strength 4,000 Lbs • High solids • Assembly time: 15-20 minutes • Clamp time: 30-60 minutes • ECOLOGO UL-2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>205 L 18.9 L 4 L 1 L 518 ml 135 ml</p>
AW 2539		<p>Outdoor wood glue</p> <ul style="list-style-type: none"> • Water-resistance PVA Type II • One part glue • Easy clean-up • Assembly time: 15-20 minutes • Clamp time: 25-60 minutes • ECOLOGO UL-2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>205 L 18.9 L 4 L 518 ml</p>
AW 0028		<p>PVA TYPE 1 glue</p> <ul style="list-style-type: none"> • Marine grade • High performance • Indoor / outdoor • Clamp time: 20-30 minutes • Cold press, Hot press, RF • Dry time: 6-8 hours • Assembly time: 5-10 minutes • Highest water-resistance ASTM D4317 • ECOLOGO UL-2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>205 L 15 L 4 L 518 ml 135 ml</p>
AW 3466		<p>PVA TYPE 2 glue</p> <ul style="list-style-type: none"> • Food grade • Ideal for cutting boards • ASTM D4317 water-resistance • Indoor / outdoor • Open time: 5-10 minutes • Clamp time: 20-30 minutes 	<p>Available sizes</p> <p>205 L 15 L 4 L 518 ml 135 ml</p>
AW 2992		<p>Craft glue (white)</p> <ul style="list-style-type: none"> • Ideal for home, school and office • Dries clear • Strength 2,800 Lbs • Assembly time: 5-10 minutes • Clamp time: 30-45 minutes • ECOLOGO UL-2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>205 L 4 L 518 ml 135 ml</p>
AW 2461		<p>White glue</p> <ul style="list-style-type: none"> • General assembly glue • Strength: 3,000 Lbs • Assembly time: 15-20 minutes • Clamp time: 50-60 minutes • ECOLOGO UL-2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>205 L 18.9 L 4 L</p>
AW 2094		<p>Carpenter's glue (yellow)</p> <ul style="list-style-type: none"> • Quick setting time • Strength 3,500 Lbs • Assembly time: 15-20 minutes • Clamp time: 25-60 minutes • ECOLOGO UL-2762 certified adhesive by UL Environment 	<p>Available sizes</p> <p>205 L 18.9 L 4 L 518 ml 135 ml</p>
AW 3515		<p>Melamine Glue</p> <ul style="list-style-type: none"> • Ideal for difficult substrates • Dries clear • High strength • Assembly time: 20-60 minutes • Drying time: 3-4 hours 	<p>Available sizes</p> <p>205 L 15 L 4 L 518 ml</p>

DURAPRO[®]

a Dural brand



The essentials for ...

- Panels
- Windows
- Subfloor
- Cabinets
- Doors
- Countertops
- Drywall
- Insulation boards
- Tiles
- Mouldings
- Concrete
- Wood floors



Made in Canada by: / Fabriqué au Canada par:

Dural Division of / Division de:
MULTIBOND, Inc.
Dorval, Quebec H9P 1C9
duraproadhesives.com / adhesifsdurapro.com



durapro@dural.ca
www.duraproadhesives.com

1-800-361-2340